



**BSP
Panel
Series**

BSP Panel Series - 10 Watt LSS

The 10 Watt LSS panel is designed to fulfill an ever-growing need for portable, damage-resistant solar modules. Backed by a stainless steel substrate and protected by a laminated Tedlar cover, the 10 watt LSS offers a perfect solution for marine, camping, military, and vandal-resistant applications.



The BSP Panel Series features:

- High performance multi-crystalline cells
- High energy yields in a wide variety of climates
- Stainless steel substrate protected by a laminated Tedlar cover

ELECTRICAL CHARACTERISTICS

Maximum power (P_{max}) ⁽¹⁾	10W
Open circuit voltage (V_{oc})	21.3V
Maximum power voltage (V_{mp})	17.3V
Short circuit current (I_{sc})	0.66A
Maximum power current at (I_{mp})	0.58A

1. Values at Standard Test Conditions (STC): 1000W/m² irradiance, AM 1.5 solar spectrum and 25°C module temperature

MECHANICAL CHARACTERISTICS

Output Cables:	AWG#18(0.75mm ²) 2core
	Cable Length: 10ft / 304.8cm
Length: inches (mm)	17.5 (444.5)
Width: inches (mm)	10.5 (266.7)
Thickness: inches (mm)	0.125 (3.175)
Weight: lbs (kg)	2.5 (1.13)

WARRANTY

5 year warranty

CERTIFICATIONS



DIMENSIONS mm (in)

