

## The Strongest Attachment in Solar


IronRidge<sup>®</sup> FlashFoot2<sup>®</sup> raises the bar in solar roof protection. The unique water seal design is both elevated and encapsulated, delivering redundant layers of protection against water intrusion. In addition, the twist-on Cap perfectly aligns the rail attachment with the lag bolt to maximize mechanical strength.

### Twist-On Cap

FlashFoot2<sup>®</sup>'s unique Cap design encapsulates the lag bolt and locks into place with a simple twist. The Cap helps FlashFoot2<sup>®</sup> deliver superior structural strength, by aligning the rail and lag bolt in a concentric load path.



### Single Socket Size

A custom-design lag bolt allows you to install FlashFoot2<sup>®</sup> with the same 7/16" socket size used on other Flash Mount



### Three-Tier Water Seal


FlashFoot2<sup>®</sup>'s seal architecture utilizes three layers of protection. An elevated platform diverts water away, while a stack of rugged components raises the seal an entire inch. The seal is then fully-encapsulated by the Cap. FlashFoot2<sup>®</sup> is the first solar attachment to pass the TAS-100 Wind-Driven



### Water-Shedding Design

An elevated platform diverts water away from the water seal.

## Installation Features



### A Alignment Markers

Quickly align the flashing with chalk lines to find pilot holes.

### B Rounded Corners

Makes it easier to handle and insert under the roof shingles.


### C Reinforcement Ribs

Help to stiffen the flashing and prevent any bending or crinkling during installation.

## Benefits of Concentric Loading

Traditional solar attachments have a horizontal offset between the rail and lag bolt, which introduces leverage on the lag bolt and decreases uplift capacity.

FlashFoot2® is the only product to align the rail and lag bolt. This concentric loading design results in a stronger attachment for the system.



## Testing & Certification

### Structural Certification

Designed and Certified for Compliance with the International Building Code & ASCE/SEI-7.

### Water Seal Ratings

Water Sealing Tested to UL 441 Section 27 "Rain Test" and TAS 100-95 "Wind Driven Rain Test" by Intertek. Ratings applicable for composition shingle roofs having slopes between 2:12 and 12:12.

### UL 2703

Conforms to UL 2703 Mechanical and Bonding Requirements. See Flush Mount Install Manual for full ratings.