

12LP10 SERIES | INVERTER

PURE SINE WAVE OUTPUT

Introduction

The Dimensions 12LP10 Series Inverter from Sensata Technologies provides pure sine wave power in a compact chassis to help power all of your sensitive electronic loads.



Features

- GFCI Outlet – Provides 120 VAC output as well as receptacle protection.
- Unit Protection – Provides automatic electronic short circuit/overload protection, automatic over-temperature shutdown, and an AC output circuit breaker.
- Status LED – Provides inverter operation mode and troubleshooting information at a glance.
- Low Battery Protection – Automatically shuts down at 10.5 VDC with in-rush delay. The end user may also select an optional setting of 11.7 VDC.
- Battery Surge Protection – The 12LP10 has an input DC voltage range of 10.5 - 16 volts. The inverter can tolerate up to 24 VDC for five minutes, then will shut down to preserve the system.
- Auto Sleep Mode – Auto sleep mode helps preserve battery life over long periods of no load operation.

Model Numbers

- 12LP10
- 12LP10H
- 12LP10HR



Pure Sine Wave



SPECIFICATIONS

	12LP10	12LP10H NO GFCI, HARDWIRE ONLY	12LP10HR NO GFCI, HARDWIRE ONLY, LOCAL ON/OFF SWITCH DISABLED
INVERTER SPECIFICATIONS			
Input battery voltage range	10.5 - 16 VDC	10.5 - 16 VDC	10.5 - 16 VDC
Surge voltage	Up to 24 VDC	Up to 24 VDC	Up to 24 VDC
Nominal AC output voltage	120 VAC ± 5%	120 VAC ± 5%	120 VAC ± 5%
Output frequency and accuracy	60 Hz ± 0.5%	60 Hz ± 0.5%	60 Hz ± 0.5%
Total Harmonic Distortion (THD)	< 5%	< 5%	< 5%
Continuous power output (real watts)	1000	1000	1000
Output current	8.3 AAC	8.3 AAC	8.3 AAC
Input current	Up to 110 ADC	Up to 110 ADC	Up to 110 ADC
Peak power	2000 watts	2000 watts	2000 watts
Peak output	23.5 AAC	23.5 AAC	23.5 AAC
Motor starting rating	1/3 hp	1/3 hp	1/3 hp
Inverter efficiency (peak)	82%	82%	82%
Waveform	Pure Sine Wave	Pure Sine Wave	Pure Sine Wave
GENERAL FEATURES			
Warranty	Five years		
Listings	UL/cUL 458 Power Inverter, E100666		
PHYSICAL SPECIFICATIONS			
Weight	20 lb (9.1 kg)	20 lb (9.1 kg)	20 lb (9.1 kg)
Dimensions (l x w x h)	17.3" x 9.0" x 3.6" (43.9 cm x 22.9 cm x 9.1 cm)		
Operating temperature	-20° C to +60° C (-4° F to 140° F)		



GENERAL NOTES

Testing for specifications at 25° C.
Specifications subject to change without notice.



AGENCY APPROVALS & CERTIFICATIONS

- UL/cUL 458 Power Inverter, E100666

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

Copyright © 2021 Sensata Technologies, Inc.