



**Remote Control  
(optional)  
for EVO Series  
Inverter Chargers**

Model  
EVO-RC

### Design Features

- Program various parameters and modes of operation
- Provides real time and data logged performance details
- SD Card Slot (accepts SD Card up to 32GB) to record data
- Indicates the status of Inverter & Charging Modes
- Power ON/OFF, or switch to Standby Mode
- Includes 33 ft of RJ-45 data cable

Capture EVO performance data on a removable SD card. Record historic power consumption, inverter functionality, battery charging activity and many other parameters. Identifies detected faults and the conditions leading up to them. Analyze trends for more efficient use of off-grid resources.

### 3 YEAR LIMITED WARRANTY

	MODEL NO.	EVO-RC
<b>COMPATIBLE INVERTER CHARGERS</b>	MODEL NUMBERS	EVO-2212, EVO-3012, EVO-2224, EVO-4024 EVO-2212E, EVO-3012E, EVO-2224E, EVO-4024E
<b>DISPLAY</b>	LCD DISPLAY	2 Rows, 16 Character each, Alpha-Numeric LCD Display
	LED INDICATORS	Green (Status); Red (Fault / Alarm)
<b>INPUT / OUTPUT CONNECTION</b>	CABLE SET	RJ-45 Data Cable (Straight Wired); 10 Meters / 33 ft
<b>ENVIRONMENT</b>	OPERATING TEMPERATURE RANGE	-20°C to 60°C
<b>DIMENSIONS</b>	(W X H X D), MM	144 x 114 x 35.5
	(W X H X D), INCHES	5.6 x 4.5 x 1.4
<b>WEIGHT</b>	WEIGHT WITHOUT CABLE	0.2 kg / 0.4 lb
	WEIGHT WITH CABLES	0.5 kg / 1.2 lb