



120W



DC-AC Inverter
Pure Sine Wave

Model
PST-120-12
12 VDC
120 VAC

Design Features

- Low-Profile Design
- USB Charging Port: 5V, 500mA
- Temperature controlled fan – runs quieter, reduces energy consumption
- 12V cigar plug adapter included
- LED indicators for power and protection
- Low battery alarm / shut down
- Low idle power draw of less than 0.5 Amps
- Approved for use in hospitals and applications requiring ANSI/AAMI ES60601-1 compliance

3 YEAR LIMITED WARRANTY



MODEL NO.		PST-120-12
AC OUTPUT	OUTPUT VOLTAGE	120V ± 3%
	OUTPUT CURRENT	1A
	OUTPUT FREQUENCY	60 Hz ± 1%
	TYPE OF OUTPUT WAVEFORM	Pure Sine Wave
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVE FORM	< 3%
	CONTINUOUS OUTPUT POWER (AT POWER FACTOR = 1)	120 Watts
	SURGE OUTPUT POWER (AT POWER FACTOR = 1)	120 Watts
	PEAK EFFICIENCY	88%
AC OUTPUT CONNECTION		NEMA1-15R Receptacle
DC INPUT	NOMINAL DC INPUT VOLTAGE	13 VDC
	DC INPUT VOLTAGE RANGE	10 - 16.5 VDC
	MAXIMUM INPUT CURRENT	15A
	DC INPUT CURRENT AT NO LOAD	< 500 mA
DC INPUT CONNECTION		Battery Modular Connector on the inverter - 2 ft. detachable Power Cord with AWG #14 wires, Mating Battery Modular Connector on inverter side and 12V Plug Adapter on battery side
DISPLAY	3 COLOR LED	For Operational Conditions
PROTECTIONS	LOW DC INPUT VOLTAGE	Shutdown at ≤ 10V; Auto-reset at ≥ 11.5V
	HIGH DC INPUT VOLTAGE	Shutdown at ≥ 16.5V; Auto-reset at ≤ 16.5V
	SHORT CIRCUIT / OVERLOAD	Output voltage drops, but does not shut down. Auto-reset on removal.
	OVER TEMPERATURE	Shut down when internal hot spot is ≥ 105°C / 221°F. Auto-reset on cooling.
	REVERSE POLARITY ON DC INPUT SIDE	Automotive Mini Blade Fuse: 32V, 15A
HIGH DC OUTPUT OF USB PORT		Shuts down USB Port at ≥ 6.2V
COOLING		Temperature Controlled Fan
COMPLIANCE	SAFETY	Intertek - ETL Listed Recognized Component. Conforms to ANSI/AAMI Standard ES60601-1
	EMI	FCC Part 15(B), Class B / EN 55022: 2006; EN 55024: 1998+A1; 2001 +A2; 2003
	EMC	EN 61000-3-2: 2006 / EN 61000-3-3: 1995+A1; 2001 +A2: 2005
ENVIRONMENT	OPERATING TEMPERATURE RANGE	0°C to 40°C / 32°F to 104°F
DIMENSIONS & WEIGHTS	(W X D X H), MM	105 x 189 x 30.5
	(W X D X H), INCHES	4.13 x 7.44 x 1.2
	WEIGHT, KG/LBS	0.453 / 1.0

NOTE: Specifications are subject to change without notice