



3000W  
samlexamerica®



### DC-AC Inverter Pure Sine Wave

Model	SA-3000K-112
	12 VDC-120 VAC
	SA-3000K-124
	24 VDC-120 VAC

### Design Features

- Pure sine wave output (THD < 3%)
- Switch selectable output frequency: 50 / 60 Hz
- Switch selectable Power Save Mode wherein the inverter shuts off non essential circuitry and reduces its no load self consumption till it sees a minimum programmed load (40 - 280 Watts)
- Optional wired remote controls for switching and monitoring the operation. Includes Ignition Lockout and Reverse Over-ride Function (ROF)
- Input and output are fully isolated
- Advanced micro-controller
- 2 load controlled cooling fans save power consumption
- 3 tri-color LEDs display operational status and fault indications

2 YEAR LIMITED WARRANTY



	MODEL NO.	SA-3000K-112	SA-3000K-124
OUTPUT	OUTPUT VOLTAGE		120 VAC, +/- 5%
	OUTPUT FREQUENCY		50 / 60 Hz +/- 0.05% (Selected by Switch)
	TYPE OF OUTPUT WAVEFORM		Pure Sine Wave
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVEFORM		< 3%
	CONTINUOUS OUTPUT POWER (At Power Factor = 1)	3000 W	3000 W
	SURGE OUTPUT POWER (At Power Factor = 1)	6000 W for 3 sec	6000 W for 3 sec
	PEAK EFFICIENCY (At full load)	88%	91%
	AC OUTPUT CONNECTIONS	Dual NEMA5-20R receptacles with GFCI protection; Terminal strip for hardwiring	
INPUT	NOMINAL DC INPUT VOLTAGE	12 VDC	24 VDC
	DC INPUT VOLTAGE RANGE	10.5 to 15 VDC, +/- 0.2 VDC	21 to 30 VDC, +/- 0.4 VDC
	DC INPUT CURRENT AT NO LOAD (Power Save on)	0.55 A	0.35 A
	DC INPUT CURRENT AT NO LOAD (Power Save off)	3.0 A	1.6 A
	DC INPUT CONNECTIONS	M-8 bolt and nut / Wire with M-8 ring lug terminal	
POWER SAVE (SLEEP MODE)	ENABLED / DISABLED BY SWITCH	Wake up power: 40 to 280 W (switch selectable)	
DISPLAY	INPUT VOLTAGE, OUTPUT POWER, STATUS	By steady / flashing patterns of three, 3- color LEDs	
REMOTE OPERATION	WIRED REMOTE CONTROL (Simple version) (Optional)	SR-8 with 10 ft cable	
	WIRED REMOTE CONTROL (Upgraded version) (Optional)	SR-6-12 with 10 ft cable	SR-6-24 with 10 ft. cable
PROTECTIONS	LOW DC INPUT VOLTAGE ALARM	10.5 VDC, +/- 0.2 VDC	21.0 VDC, +/- 0.4 VDC
	LOW DC INPUT VOLTAGE SHUTDOWN	10.0 VDC, +/- 0.2 VDC	20.0 VDC, +/- 0.4 VDC
	HIGH DC INPUT VOLTAGE SHUTDOWN	15.0 VDC, +/- 0.2 VDC	30.0 VDC, +/- 0.4 VDC
	SHORT CIRCUIT SHUTDOWN		Yes
	OVERLOAD SHUTDOWN		Yes
	GROUND FAULT SHUTDOWN		Yes. Only for the GFCI protected dual NEMA5-20R receptacles
	OVER TEMPERATURE SHUTDOWN		Yes
REVERSE POLARITY ON DC INPUT SIDE		Yes. Internal fuses will blow	
COOLING	FORCED AIR COOLING	2 load controlled fans: ON > 450W ; OFF < 240W	
COMPLIANCE	SAFETY	Meets UL-458	
	EMI / EMC	Meets FCC Part 15(B), Class A	
ENVIRONMENT	OPERATING TEMPERATURE RANGE	0 °C to + 40 °C	
	STORAGE TEMPERATURE RANGE	- 30 °C to 70 °C	
DIMENSIONS	(L X W X H), MM	452 x 208 x 166	
	(L X W X H), INCHES	17.8 x 8.18 x 6.53	
WEIGHT	KG	9.8	
	LBS	22	

NOTE: Specifications are subject to change without notice

12003-SA-3000K-112-124-0715