

Conext System Control Panel

Monitor and Configure Conext Inverter Charger Systems and Xanbus Enabled Accessories

The Conext™ System Control Panel (SCP) eliminates the need for separate control panels for each device and gives a single point of control to set up and monitor the entire Conext inverter charger system, including Conext MPPT Solar Charge Controllers. Featuring a graphical backlit liquid crystal display, the SCP selectively displays configuration, status and diagnostic information for all devices connected to the Xanbus™ network.

Why choose Conext System Control Panel?



True bankability

- Warranty from a trusted partner with 178 years of experience
- World leader in industrial power drives, UPS and electrical distribution
- Strong service infrastructure worldwide to support your global needs



Higher return on investment

- Get the most out of Conext inverter charger systems and Conext MPPT Solar Charge Controllers
- Clearly understand status and settings
- Optimize system set up and device performance



Designed for reliability

- Extensive quality and reliability testing



Flexible

- Monitor and configure Conext XW+, SW, MPPT 60 150, MPPT 80 600, AGS, Battery Monitor
- Multiple SCP can be used on the same Xanbus network
- Compatible with Conext ComBox



Easy to service

- Access and troubleshoot Xanbus enabled devices on the network from one location
- Remove and replace without the loss of device settings



Easy to install

- Surface mount or panel mount on wall
- RJ45 connections for Xanbus network cables



Product applications



Backup power




Residential grid-tie solar with backup power



off-grid solar



Community electrification



Self-consumption

Device short name	Conext System Control Panel
Electrical specifications	
Nominal voltage	15 VDC
Min. operating network voltage	14.25 VDC
Max. operating network voltage	15.75 VDC
Max. operating current at nominal voltage	200 mA
General specifications	
Dimensions (H x W x D)	15.2 x 10.3 x 4.0 cm (5.9 x 2.6 x 1.6 in)
Weight	200 g (0.4 lb)
Shipping weight	800 g (1.8 lb)
Mounting options	Panel-mount, wall-mount
IP rating / location	IP20, indoor only
Operating temperature range	-20 to 50°C (-4°F to 122°F)
Part number	865-1050-01
Features	
Network	Protocol: Xanbus / Connectors: RJ45
Internal clock	Provides network time
Memory	Non volatile
Alarm	Audible
Display	Backlit LCD. Green / red LED
Front-panel interface	Four menu buttons, One standby button
Warranty	2 to 5 years (depending on country)
Regulatory approvals	
Safety	CSA 107.1, UL 458 4 th Ed
EMC	CE directive 2004 / 108 / EC, IEC / EN61000-6-3, IEC / EN61000-6-1, FCC Part 15B Class B, Industry Canada ICES-00. Class B, C-Tick
Included parts	
	One remote head
	One network terminal
	One CAT5 cable (2.1 m)
	One mounting plate
	One mounting bracket
	Four #8 screws
	Two #6 screws

Specifications are subject to change without notice.

Conext Automatic Generator Start works with the following Schneider Electric products



Conext XW inverter/charger

XW 5548 NA Product no. 865-5548-01
 XW 6848 NA Product no. 865-6848-01
 XW 7048 E Product no. 865-7048-61
 XW 8548 E Product no. 865-8548-61



Conext SW inverter/charger

SW 2524 120 Product no. 865-2024
 SW 4024 120 Product no. 865-4024
 SW 2524 230 Product no. 865-2524-61
 SW 4024 230 Product no. 865-4024-61



MPPT 60 150 solar charge controller
 Product no. 865-1030-1



MPPT 80 600 solar charge controller
 Product no. 865-1032



Conext Automatic Generator Start (AGS)
 Product no. 865-1060-01



Conext Combox communication device
 Product no. 865-1058



Conext Battery Monitor
 Product no. 865-1080-01