


**36 CELL**  
POLYCRYSTALLINE MODULE

**90W**  
POWER OUTPUT

**20.00%**  
MODULE EFFICIENCY

**5%**  
POSITIVE TOLERANCE



# SLP090-12C1D2

## High Efficiency Polycrystalline PV Module

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Designed to withstand high wind pressures, hail and heavy snow.
- Quality aesthetic appearance.



**High Efficiency**

Module Efficiency improved through advanced cell technology and manufacturing capabilities



**High PID Resistance**

Advanced cell technology and qualified materials lead to high resistance to PID




**Withstands Harsh Environment**

High PID resistance  
5400 Pa positive load  
2400 Pa negative load  
Salt mist (IEC 61701)

### Performance Warranty

**10 years**  
Product Warranty

**25 years**  
Power Warranty



Product Certificate

IEC 61215, IEC 61730, C1D2 - Class 1, Division 2, UL1703, cUL1703, Hazardous Environments

Management Certificate

ISO 9001: 2016

Other certificate

Fire Rating Class C, TÜV Rheinland

Positive mechanical load

>5400Pa


Positive Power Tolerance

0~+5W

Warranty Information

2 Year Product Warranty and Workmanship







Electrical Characteristics	SLP090-12C1D2
Product code	090011263
Maximum power (Pmax)	90W
Voltage at Pmax (Vmp)	18.64V
Current at Pmax (Imp)	4.83A
Open-circuit voltage (Voc)	22.18V
Short-circuit current (Isc)	5.12A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

\*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C


\*NOCT: Nominal operating cell temperature (the data is only for reference)



Specifications	SLP090-12C1D2
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	940mm[37.01in.]x675mm[26.57in.]x35mm[1.38in.]
Weight	7.21kg[15.89lbs]
Packing information(Carton)	985mm[38.78in.]x720mm[28.35in.]x105mm[4.13in.]/(2pcs/ctn)




Junction Box  
Top View (Lid Open)



Section A-A

Characteristics



SLP090-12C1D2 I-V Curves

Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]