

# SLP330-24C1D2

## High Efficiency Polycrystalline PV Module


- Nominal 24V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Designed to withstand high wind pressures, hail and heavy snow.
- Quality aesthetic appearance.

**72 CELL**  
POLYCRYSTALLINE MODULE

**330W**  
POWER OUTPUT

**20.00%**  
MODULE EFFICIENCY

**5%**  
POSITIVE TOLERANCE



**High Efficiency**

Module Efficiency improved through advanced cell technology and manufacturing capabilities



**High PID Resistance**

Advanced cell technology and qualified materials lead to high resistance to PID




**Withstands Harsh Environment**

High PID resistance  
5400 Pa positive load  
2400 Pa negative load  
Salt mist (IEC 61701)

### Performance Warranty


**10** years  
Product Warranty

**25** years  
Power Warranty



Product Certificate	IEC 61215, IEC 61730, C1D2 - Class 1, Division 2, UL1703, cUL1703, Hazardous Environments
Management Certificate	ISO 9001: 2016
Other certificate	Fire Rating Class C, TÜV Rheinland
Positive mechanical load	>5400Pa
Positive Power Tolerance	0~+5W
Warranty Information	2 Year Product Warranty and Workmanship





**Electrical Characteristics**

SLP330-24C1D2



Product code	330012463
Maximum power (Pmax)	330W
Voltage at Pmax (Vmp)	37.79V
Current at Pmax (Imp)	8.73A
Open-circuit voltage (Voc)	44.97A
Short-circuit current (Isc)	9.27A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/ °C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

\*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C  
\*NOCT: Nominal operating cell temperature (the data is only for reference)


**Specifications**

SLP330-24C1D2

Cells	Polycrystalline silicon solar cell
No. of cells and connections	72(6X12)
Module dimension	1956mm[77.01in.]x992mm[39.06in.]x40mm[1.57in.]
Weight	21.50kg[47.40lbs]
Packing information(Carton)	1996mm[78.58in.]x1032mm[40.63in.]x90mm[3.54in.]/(1pc/ctn)




Junction Box  
Top View (Lid Open)



Section A-A

**Characteristics**



SLP330-24C1D2 I-V Curves

Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]