

# CHILICON POWER CP-250E

## Single Channel Microinverter



### CP-250E™ Series Microinverters

The Chilicon CP-250E allows installers to maximize PV system production, while minimizing installation and operational costs. Microinverter based architectures offer the benefit of increased flexibility in panel deployment, while also providing per panel visibility to simplify system O&M. With its all-AC approach, integrated grounding, modular bus cabling, and ability to support up to 20 panels on a 30A branch circuit, the CP-250E simplifies both design and installation. Both freq-Watt and volt-Watt modes allow AC control by off-grid systems. Coupled with Chilicon's CP-100 gateway and cloud-based monitoring software, the CP-250E can form the energy management backbone of both residential and commercial PV systems.

### Performance

- Supports panels up to 350W with no clipping
- Maximizes energy production over life of system
- Minimizes losses due to shading and debris
- Eliminates single point of failure for system

### Simplicity

- All AC design – No string calculations needed
- No GEC needed for microinverters
- Easy installation with standardized trunk cables

### Versatility

- Compatible with most 60 or 72 cell panels
- Available in 240V or 208V
- Allows for variable module placement
- Robust PLC communication protocol (500 ft range)
- Self supply mode (zero-export)
- Supports up to 30A branch circuits

### Reliability, Safety, & Compliance

- NEMA 6 rated construction
- 25 year warranty
- AC branch circuits will not support arc faults
- Quick disconnect circuit to mitigate grid instabilities
- NEC 690.12 rapid shutdown compliant
- CA Rule 21 (UL 1741-SA) compliant





## CP-250E-60-72-208/240-MC4 Microinverter Specifications

### INPUT DATA (DC)

Recommended input power (STC)	190 - 355 W
Maximum DC input voltage	60 V
MPPT voltage range	22 – 38.5 V
Operating range	18 – 38.5 V
Min./Max. start voltage	22 – 47 V
Max. DC input short circuit current	21 A
Max. DC input current	12 A
Ground fault protection	Transformer isolated 2000 Vrms input/output/chassis

### OUTPUT DATA (AC)

	@ 208 V	@ 240 V
Max. continuous output power	277 W	289 W
Max. continuous output current	1.33 A	1.20 A
Nominal output voltage / range	208 / 183 – 229 V	240 / 211 – 264 V
Extended output voltage range	133 / 150 / 166 – 250 V	153 / 173 / 192 – 288 V
Nominal frequency* / range	60.0 / 59.3 – 60.5 Hz	60.0 / 59.3 – 60.5 Hz
Extended frequency range	54.22 – 66.75 Hz	54.22 – 66.75 Hz
Power factor	-0.8 to 0.8 programmable	-0.8 to 0.8 programmable
Maximum units per branch circuit	18 (30A 10 AWG) / 12 (20A 12AWG)	20 (30A 10AWG) / 13 (20A 12AWG)
Maximum output fault current & duration	1.6 A peak for > 10% of any cycle	1.6 A peak for > 10% of any cycle
Maximum output overcurrent protection	6.3 A	6.3 A
		Bond Trunk Red to White for 1 $\Phi$ system
*50Hz operation; 50.0 / 49.5 – 50.5 Hz	45.2 – 55.7 Hz extended range	

### EFFICIENCY

CEC weighted efficiency	96 %
Peak inverter efficiency	96.6 %
Static MPPT efficiency (EN 50530)	99.5 % - 99.8 %
Night time power consumption	40 mW @ 208V, 80 mW @ 240 V

### MECHANICAL DATA

Ambient temperature range	-40° C to +65° C
Dimension (W x H x D) including connectors	12" x 8" x 1.8"
Weight	1.55 kg (3.4 lbs)
Enclosure rating	NEMA 6

### FEATURES

Power Control	Self-Supply / Zero-Net-Export; Freq/Volt-Watt Control with 60-cell modules
Monitoring	Power line (130.2 kHz carrier); Free monitoring via gateway or online software
Compliance	UL1741SA Rule-21, IEEE std 1547, IEEE std C62.41.2, CSA C22.2 NO. 107.1 & CISPR 22 Class B HECO Rule14H (Advanced Inverter), HECO Rule 22 (Self-Supply), NEC 2014 and NEC 2017 Rapid Shutdown Compliant

Compatibility

60/72 cell PV modules with compatible input voltage range specifications above