

Deka®

SOLAR

PHOTOVOLTAIC BATTERIES

8L16

- Reinforced case resists bulging and meets safety requirements
- Case & cover heat sealed and 100% tested to prevent leaks
- Puncture resistant microporous polyethylene separators extend life
- Computer-aided design and manufacturing control processes and standards to ensure quality products
- Designed to provide reliable, long lasting back-up power for Photovoltaic (PV) and Renewable Energy applications where frequent deep cycles are required and minimum maintenance is desirable
- Applications: Water Pumping, Residential / Small Village, Cathodic Protection, Remote Monitoring, Lighting, Wind Generation, & Railway Signal



SPECIFICATIONS

Nominal Voltage: 6-Volt
Rating: 370 Ah @ 20 HR rate to 1.75 V.P.C.
Positive Plate: Antimony Alloy
Negative Plate: Antimony Alloy
Specific Gravity: 1.275 at 77°F (25°C) fully charged
Case/Cover: Polypropylene
Safety Vent: Individual quarter – turn bayonet
Post Torque: 50 in lb


PHOTOVOLTAIC CHARGING PARAMETERS

Charge Type	Max. Current (AMPS)	Voltage Range
Bulk Charge	30% of 20HR Rate	
Absorption (Regulation) Charge	Constant Voltage	2.40 – 2.45 V.P.C.
Float Charge	Constant Voltage	2.30 – 2.35 V.P.C.
Equalize Charge	Constant Voltage	2.50 – 2.55 V.P.C.
Temperature Coefficient	- 0.003 V / °C	

TYPE NO.		TERMINAL TYPE	PERFORMANCE (Ah) ¹ to 1.75 V.P.C.		SHORT CIRCUIT CURRENT	ELECTROLYTE VOLUME		APPROXIMATE WEIGHT			
WET	DRY ²		20 HR.	100 HR.		QUART	LITER	WET		DRY	
								LB.	KG.	LB.	KG.
6-VOLT SOLAR FLOODED MONOBLOC											
8L16	8L16D	T	370	420	2339	11.5	10.9	113	51	83.0	38

1 – Ratings after 15 Cycles
 2 – "D" suffix indicated dry option available
 N/A – Not Applicable

Terminal: T





QUALITY SYSTEM
 CERTIFIED
ISO 9001
ISO/TS 16949
 ENVIRONMENTAL
 SYSTEM CERTIFIED
ISO 14001

