

# SUNNY HIGHPOWER PEAK3

## 125-US / 150-US / 165-US / 172-US



SHP 125-US-21 / SHP 150-US-21 / SHP 165-US-21 / SHP 172-US-21



**25** YEAR  
DESIGN LIFE



**SMA**  
Smart Connected



### Cost effective

- Modular architecture reduces BOS and maximizes system uptime
- Compact design and high power density maximize transportation and logistical efficiency

### Maximum flexibility

- Scalable 1,500 VDC building block with best-in-class performance
- Flexible architecture creates scalability while maximizing land usage

### Simple install, commissioning

- Ergonomic handling and simple connections enable quick installation
- Centralized commissioning and control with SMA Data Manager

### Highly innovative

- SMA Smart Connected reduces O&M costs and simplifies field-service
- Powered by award winning ennexOS cross sector energy management platform

## SUNNY HIGHPOWER PEAK3

### 125-US / 150-US / 165-US / 172-US

A superior modular solution for large-scale power plants

The PEAK3 1,500 VDC inverter offers high power density in a modular architecture that achieves a cost-optimized solution for large-scale PV integrators. With fast, simple installation and commissioning, the Sunny Highpower PEAK3 is accelerating the path to energization. SMA has also brought its field-proven Smart Connected technology to the PEAK3, which simplifies O&M and contributes to lower lifetime service costs. The PEAK3 power plant solution is powered by the ennexOS cross sector energy management platform, 2018 winner of the Intersolar smarter E AWARD.

Technical Data	Sunny Highpower PEAK3 125-US	Sunny Highpower PEAK3 150-US	Sunny Highpower PEAK3 165-US	Sunny Highpower PEAK3 172-US
<b>Input (DC)</b>				
Maximum array power <sup>1)</sup>	250 kWp	300 kWp	330 kWp	344 kWp
Maximum system voltage	1500 Vdc			
Rated MPP voltage range	705 V ... 1450 V	880 V ... 1450 V	924 V ... 1450 V	968 V ... 1450 V
MPPT operating voltage range	684 V ... 1500 V	855 V ... 1500 V	898 V ... 1500 V	941 V ... 1500 V
MPP trackers	1			
Maximum operating input current	180 A			
Maximum input short-circuit current	325 A			
<b>Output (AC)</b>				
Nominal AC power	125 kW	150 kW	165 kW	172 kW
Maximum apparent power	125 kVA	150 kVA	165 kVA	172 kVA
Output phases / line connections	3 / 3-PE			
Nominal AC voltage	480 V	600 V	630 V	660 V
Compatible transformer winding configuration	Wye-grounded			
Maximum output current	151 A			
Rated grid frequency	60 Hz			
Grid frequency / range	50 Hz, 60 Hz / -6 Hz ... +6 Hz			
Power factor at rated power / adjustable displacement	1 / 0.8 leading ... 0.8 lagging			
Harmonics (THD)	<3%			
<b>Efficiency</b>				
CEC efficiency	98.5 %	99.0 %	99.0 %	99.0 %
<b>Protection and safety features</b>				
Ground fault monitoring: Riso / Differential current	● / ●			
DC reverse polarity protection	●			
AC short circuit protection	●			
Monitored surge protection (Type 2): DC / AC	● / ●			
Protection class / overvoltage category (as per UL 840)	I / IV			
<b>General data</b>				
Device dimensions (W / H / D)	770 / 830 / 462 mm (30.3 / 32.7 / 18.2 in)			
Device weight	99 kg (218 lbs)			
Operating temperature range	-25 °C ... +60 °C (-13 °F ... +140 °F)			
Storage temperature range	-40 °C ... +70 °C (-40 °F ... +158 °F)			
Audible noise emission (full power @ 1 m and 25 °C)	< 69 dB(A)			
Internal consumption at night	< 5 W			
Topology	Transformerless			
Cooling concept	OptiCool (forced convection, variable speed fans)			
Enclosure protection rating	Type 4X			
Maximum permissible relative humidity (non-condensing)	100%			
<b>Additional information</b>				
Mounting	Rack mount			
DC connection	Terminal lug (up to 600 kcmil CU/AL)			
AC connection	Screw terminal (up to 300 kcmil CU/AL)			
LED indicators (Status/Fault/Communication)	●			
SMA Speedwire (Ethernet network interface)	● (2 x RJ45 ports)			
Data protocols: SMA Modbus / SunSpec Modbus	● / ●			
Integrated Plant Control / Q on Demand 24/7	● / ●			
Off-grid capable / SMA Hybrid Controller compatible	- / ●			
<b>Monitoring</b>				
SMA Sunny Portal (monitoring portal)	No cost for the lifetime of the system			
SMA Smart Connected (monitoring and remote O&M service)	No cost on inverters under warranty			
Supported protocols for outbound data	SMA external API, Modbus, FTP			
<b>Certifications</b>				
Certifications and approvals (pending)	UL 62109, UL 1998, CAN/CSA-C22.2 No.62109			
Manufacturer's Declaration of Design Life	25 years			
FCC compliance	FCC Part 15, Class A			
Grid interconnection standards	IEEE 1547:2018, UL 1741-SA - CA Rule 21, HECO Rule 14H, UL1741SB			
Advanced grid support capabilities	L/HVRT, L/HVRT, Volt-VAr, Volt-Watt, Frequency-Watt, Ramp Rate Control, Fixed Power Factor			
<b>Warranty</b>				
Standard	5 years			
Optional extensions	10 / 15 / 20 / 25 years			
1) Higher DC array power permitted via site inverter load modeling in SMA Sunny Design				
Type designation	SHP 125-US-21	SHP 150-US-21	SHP 165-US-21	SHP 172-US-21
● Standard features   ○ Optional features   – Not available				

SHP-US-Dee-22 - Changes to products and services, including those resulting from country-specific requirements, as well as deviations from technical data are subject to change at any time without notice. SMA assumes no liability for typographical or other errors. Please visit www.sma-solar.com for the latest information.