

---

# Power Optimizer

P370 / P401 / P404 / P405 / P485 / P500 / P505

POWER OPTIMIZER



## PV power optimization at the module level

- Specifically designed to work with SolarEdge inverters
- Superior efficiency (99.5%)
- Up to 25% more energy
- Flexible system design for maximum space utilization
- Next generation maintenance with module-level monitoring
- Module-level voltage shutdown for installer and firefighter safety
- Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading
- Fast installation with a single bolt

# / Power Optimizer

P370 / P401 / P404 / P405 / P485 / P500 / P505

OPTIMIZER MODEL (typical module compatibility)	P370 (60/72 Cell modules)	P401 (For high power 60/72-cell modules)	P404 (for 60/72- cell short strings)	P405 (for high-voltage modules)	P485 (for high-voltage modules)	P500 (for 96-cell modules)	P505 (for higher current modules)	UNIT
<b>INPUT</b>								
Rated Input DC Power <sup>(1)</sup>	370	400	405	405	485	500	505	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	60		80	125		80	83	Vdc
MPPT Operating Range	8 - 60		12.5 - 80	12.5 - 105		8 - 80	12.5-83	Vdc
Maximum Short Circuit Current (Isc)	11	11.75	11			10.1	14	Adc
Maximum Efficiency					99.5			%
Weighted Efficiency					98.8			%
Overtoltage Category					II			
<b>OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)</b>								
Maximum Output Current					15			Adc
Maximum Output Voltage	60		85		60	85		Vdc
<b>OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)</b>								
Safety Output Voltage per Power Optimizer					1 ± 0.1			Vdc
<b>STANDARD COMPLIANCE</b>								
EMC					FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3			
Safety					IEC62109-1 (class II safety), UL1741			
RoHS					Yes			
Fire Safety					VDE-AR-E 2100-712:2013-05			
<b>INSTALLATION SPECIFICATIONS</b>								
Maximum Allowed System Voltage					1000			Vdc
Dimensions (W x L x H)	129 x 153 x 27.5 / 5.1 x 6 x 1.1	129 x 153 x 29.5 / 5.08 x 6.02 x 1.16	129 x 89 x 42.5 / 5.1 x 3.5 x 1.7	129 x 90 x 49.5 / 5.1 x 3.5 x 1.9		129 x 153 x 33.5 / 5.1 x 6 x 1.3	129 x 162 x 59 / 5.1 x 6.4 x 2.3	mm / in
Weight (including cables)	655 / 1.5		775 / 1.7	845 / 1.9		750 / 1.7	1064 / 2.3	gr / lb
Input Connector	MC4 <sup>(2)</sup>				Single or Dual MC4 <sup>(2)(3)</sup>	MC4 <sup>(2)</sup>		
Input Wire Length					0.16 / 0.52			m / ft
Output Connector					MC4			
Output Wire Length					1.2 / 3.9			m / ft
Operating Temperature Range					-40 - +85 / -40 - +185			°C / °F
Protection Rating					IP68			
Relative Humidity					0 - 100			%

(1) Rated power of the module at STC will not exceed the optimizer "Rated Input DC Power". Modules with up to +5% power tolerance are allowed.

(2) For other connector types please contact SolarEdge.

(3) For dual version for parallel connection of two modules use the P485. In the case of an odd number of PV modules in one string, installing one P485 dual version power optimizer connected to one PV module is supported. When connecting a single module, seal the unused input connectors using the supplied pair of seals.

PV SYSTEM DESIGN USING A SOLAREEDGE INVERTER <sup>(4)(5)</sup>		SINGLE PHASE HD-WAVE	SINGLE PHASE	THREE PHASE	THREE PHASE FOR 277/480V GRID	
Minimum String Length (Power Optimizers)	P370, P401, P500 <sup>(6)</sup>	8		16	18	
	P404, P405, P485, P505	6		14 (13 with SE3K <sup>(7)</sup> )	14	
Maximum String Length (Power Optimizers)			25	50	50	
Maximum Power per String	5700		5250	11250 <sup>(8)</sup>	12750 <sup>(9)</sup>	W
Parallel Strings of Different Lengths or Orientations					Yes	