SLP030-12C1D2

High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP030-12C1D2
Produc code	030011263
Maximum power (Pmax)	30W
Voltage at Pmax (Vmp)	18.64V
Current at Pmax (Imp)	1.61A
Open-circuit voltage (Voc)	22.18V
Short-circuit current (Isc)	1.71A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/ °C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C
*NOCT:Nominal operating cell temperature (the data is only for reference)

Module Diagram



Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]



Junction Box
Top View(Lid Open)



Section A-A

Features

- Nominal 12V DC for standard output.
- Heavy-duty anodized frames.
- High transparent low-iron,tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



SLP030-12C1D2 I-V Curves

Specifications	SLP030-12C1D2
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(2X18)
Module dimension	675mm[26.57in.]x357mm[14.06in.]x30mm[1.18in.]
Weight	2.8kg[6.17lbs]
Packing information(Carton)	690mm[27.17in.]x145mm[5.71in.]x380mm[14.96in.]/(5pcs/ctn)

*Limited warranty: 2-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.
*Specifications are subject to change without notice at any time.