




# W-Series 20W PV Module SPM020P-WP-N

## Solartech W-Series Modules

Solartech photovoltaic W-Series Modules are constructed with high efficient polycrystalline solar cells and produce higher output per module than others in its class. This industrial grade module is an industry standard among various industry professionals.

### Features

- (EVA) with TPT cushions the solar cells within the laminate and ensures the operating characteristics of the solar cells under virtually any climatic condition
- Rigid anodized aluminum frame and low iron tempered glass
- Easily accessible grounding points on all four corners for fast installation
- Proven junction box technology



### Reliability

- Proven superior field performance
- Tight power tolerance

### Qualifications and Certifications



### Applications

- Traffic & Safety
- Federal Government
- Agricultural
- Security
- Telecommunications
- Water and Wastewater
- Weather & Environmental Monitoring
- RV Camper
- Emergency Power
- Telemetry
- SCADA, RTU, GPS
- Marine
- Area Lighting & Sign
- Wi-Fi & Wi=Max
- Fence & Gate


## Electrical Characteristics

Max power(Pm)	20W
Maximum power voltage(Vpm)	33.9V
Maximum power current (Ipm)	0.61A
Short circuit current (Isc)	0.65A
Open circuit voltage (Voc)	41.3V
Module efficiency	10.38%
Tolerance	±5%
Nominal Voltage	24V
Temperature coefficient of Voc	-0.36%/K
Temperature coefficient of Pm	-0.46%/K
Temperature coefficient of Isc	0.05%/K
NOCT	48°C ± 2°C
Maximum series fuse rating	10A
Maximum system voltage	600V

## Mechanical Characteristics

Construction	Tempered glass, silicon cell, EVA, Polyester with Tedlar
Solar Cells	68 cells (78mm x26mm) in a 4x17 matrix connected in series
Front Cover	High transmission 3.2mm(1/8") glass
Encapsulant	EVA(Double layers)
Back Cover	White polyester
Frame	Anodized aluminum
Junction Box	IP65, UL94-5VA material
Diodes	None
Dimensions	550mm(21.7in)x350mm(13.8in)x25mm (0.98in)
Weight	2.8 kg
Operating Temperature	-40°C~90°C
Storage Humidity	<90%

## IV Curves



## Certifications

UL 1703 certification

\*Subject to simulator measurement uncertainty of +/- 5%.  
Solartech Power, Inc. reserves the right to modify these specifications without notice.  
For more detailed specifications, visit [www.solartechpower.com](http://www.solartechpower.com)

