HOM115PDF

Mini circuit breaker, Homeline, 15A, 1 pole, 120VAC, 10kA AIR, combo ARC/ground fault, plug on neutral, plug in, UL





Main

IVICIII	
Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Combination ARC-fault and ground fault class A 6 mA
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x AWG 14AWG 8 (aluminium/copper) 2 x AWG 14AWG 10 (copper)

Complementary

Connections - Terminals	Plug-on neutral
Tightening torque	35.40 lbf.in (4.0 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.40 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Allibielli Ali Telliberature ioi Oberation	104 1 (40 0)

Ordering and shipping details

Category	06301-HOM SINGLE POLE ARC FAULT CIRCUIT BREAKER
Discount Schedule	DE3D
GTIN	785901978510
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.00 in (10.16 cm)	
Package 1 Width	1.40 in (3.556 cm)	
Package 1 Length	5.10 in (12.954 cm)	
Package 1 Weight	10.40 oz (294.835 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	40	
Package 2 Height	3.50 in (8.89 cm)	
Package 2 Width	13.70 in (34.798 cm)	

Package 2 Length	20.80 in (52.832 cm)	
Package 2 Weight	25.85 lb(US) (11.725 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free product

Contractual warranty

Warranty	Lifetime