

“Stay Connected” with



Solar Power Components

a PennEngineering® Company




HEYClip™ Stainless Steel SunRunner® 4-2 and 4-2U Cable Clips


For Oval Micro-Inverter Cables

- Designed to hold Micro-Inverter oval cables .250" (6,3 mm) x .385" (9,8 mm).
- Constructed from heat treated 410 stainless steel for excellent strength and corrosion protection for outdoor exposure.
- Smooth clip edges prevent damage to cable insulation.
- “S” hook clip design will fit a wide variety of extruded aluminum profiles.
- SunRunner 4-2 is designed for solar mounting frames such as the ones used by with Everest, SnapNrack and similar extrusions.
- SunRunner 4-2U features a shorter S hook for Unirac, IronRidge and similar frame profiles.
- Neatly dresses cables along mounting frame channels from .080" (2,5 mm) to .250" (6,4 mm) thick.
- See page 1-11 for typical rack profile applications.


CHANNEL THICKNESS CLAMPING RANGE				WIRE CAPACITY		PART NO.	DESCRIPTION	FOOTPRINT		REAR TAB LENGTH	
Minimum		Maximum		in.	mm.			in.	mm.	in.	mm.
in.	mm.	in.	mm.								
SunRunner 4-2											
.08	2,0	.25	6,4	.25 x 1.00	6,4 x 25,4	S6504	SunRunner 4-2 100 Pack	.50 x 1.34	12,7 x 34,0	.84	21,3
							S6544				
SunRunner 4-2U											
.25	6,4	.25	6,4	.25 x 1.00	6,4 x 25,4	S6505	SunRunner 4-2U 100 Pack	.50 x 1.34	12,7 x 34,0	.38	9,7
							S6545				



SunRunner 4-2



SunRunner 4-2U



Quick Specs

Material	.020" thick 410 stainless steel
Certifications	cUL _{us} Certified by UL for Compliance with both Canadian and US Requirements under File E54523
Temperature Range	-40°F (-40°C) to 572°F (300°C)