BlueSolar PWM-Light Charge Controllers 12/24V



BlueSolar PWM-Light 10A

Features

- Load output with low battery voltage disconnect function.
- Lighting control function, one timer only.
 - Two digit seven segment display for quick and easy setting of the load output functionality, including timer setting.
 - Three stage battery charging (bulk, absorption, float), not programmable.
 - Load output protected against over load and short circuit.
 - Protected against reverse polarity connection of the solar array and/or battery.

Day/night timing options

See manual for details

BlueSolar PWM-Light	12/24-5	12/24-10	12/24-20	12/24-30
Battery Voltage	12/24 V with automatic system voltage detection			
Rated charge current	5A	10A	20A	30A
Automatic load disconnect	Yes			
Maximum solar voltage	28V / 55V (1)			
Self-consumption	< 10 mA			
Load output	Manual control + low voltage disconnect			
Protection	Battery reverse polarity (fuse) Output short circuit Over temperature			
Overload protection	Shut down after 60 s in case of 130% load			
	Shut down after 5 s in case of 160% load			
	Short circuit: immediate shut down			
Grounding	Common positive			
Operating temp. range	-20 to +50°C (full load)			
Humidity (non-condensing)	Max 95%			
		BATTERY		
Charge voltage 'absorption'	14.2V / 28,4V			
Charge voltage 'float'	13.8V / 27,6V			
Low voltage load disconnect	11,2V/22,4V			
Low voltage load reconnect	12,6V / 25,2V (manual)			
	13,1V / 26,2V (automatic) ENCLOSURE			
Protection class		ENCLOSURE	IP20	
Terminal size	1P20 5 mm² / AWG10			
Weight	0,15kg 0,2kg			
Dimensions ($h \times w \times d$)	0,2kg 70 X 133 X 33,5 mm (2.8 x 5.3 x 1.3 inch)			
	STANDARDS			
Safety	IEC 62109-1			
EMC	EN 61000-6-1, EN 61000-6-3, ISO 7637-2			
		,	3 3.	
1) For 12V use 36 cell solar panels For 24V use 72 cell solar panels or 2x 36 cell in series	2) The controller switches to the lower float voltage level 2 hours after the absorption voltage has been reached. Whenever the battery voltage becomes lower than 13V, a new charge cycle is triggered.			